

Marthall Tree Products

T 01565 650526 sales@marthall.net www.marthall.net F 01565 650543

Chelford Road Ollerton Knutsford Cheshire WA16 8SZ

Rode

Yarn stitching	Tufted, non filled synthetic grass carpet
Yarn material	Polyethylene monofilament straight & polypropylene monofilament curled
Yarn type	7,000/8 dTex + 4,000/8 dTex
Yarn quality	environmental friendly, UV stabilized, UV stability meets DIN 53387 standard
Colour fastness	DIN 54004 Grade 7 (Blue Scale)
Primary backing	100% Polypropylene Colored fleece, black, UV stabilized. 210 g/m ²
Secondary backing	black latex compound with a base of styrene-butadiene (SBR), with drainage holes. 1000 g/m ²

Tuft gauge	3/8"	
Pile height	25 mm	+/-5%
Stitches per 10cm	18	+/-10%
Stitches per m ²	18,900	+/-10%
Face weight	1,100 g/m ²	+/-10%
Total weight	2,310 g/m ²	+/-10%
Roll width	4m or 2m (+0.2m)	+/- 2cm

Water permeability	60l/min/m ²
Batch information	before installation make sure the first 4 digits of the roll number are equal
Shrinkage	Shrinkage can appear due to extreme temperatures. Make sure the carpet can relax before cutting
Infill recommendation	non infill (optional 5kg/m ²)



c-shape^{1.5}

