

Marthall Tree Products

T 01565 650526 sales@marthall.net www.marthall.net F 01565 650543

Chelford Road Ollerton Knutsford Cheshire WA16 8SZ

Tatton

Yarn stitching	Tufted, non-filled synthetic grass carpet
Yarn material	65% Polyethylene/ 35% Polypropylene monofilament straight /Curled
Yarn type	7,200/8 dTex + 4,000/8 dTex
Yarn quality	UV tested >3,000 hrs UV-A. Chlore resistance 4-5 (DIN 54019). Resistance to brine 4-5 (DIN 54007)
Colour fastness	DIN 54004 Grade 7 (Blue Scale)
Primary backing	Polypropylene woven 154 g/m ²
Secondary backing	Black latex compound with a base of styrene-butadiene (SBR), with drainage holes 900 g/m ²

Tuft gauge	5/16"	
Pile height	35 mm	+/-10%
Stitches per 10cm	19	+/-10%
Stitches per m ²	23940	+/-10%
Face weight	1300 g/m ²	+/-10%
Total weight	2325 g/m ²	+/-10%
Roll width	2m & 4m (+0.2m)	+/- 2cm

Water permeability	60l/min/100cm ²
Fire retardant classification	Cfl-S1 (EN ISO 11925-2: sand filled ca. 5mm) Efl-S1 (EN ISO 11925-2; non filled)
Batch information	Before installation make sure the first 4 digits of the roll number are equal
Shrinkage	Shrinkage can appear due to extreme temperatures. Make sure the carpet can relax before cutting
Infill recommendation	Non infill (optional 5kg/m ²)



diamond-shape^{1.0}

